

## Hot cookline - fridge only

Standard drawer + heat shield top



# Applications

Hydrocarbon

R600a Refrigerant

A+ Fridge

Drawer

'A+' Energy Rating

(Consumption 239 kWh/annum)

+15<sup>°</sup>C ←

- Bulk storage at the point of use in the cookline
- Designed for heavy cooking equipment, mounted on either a Heat Shield or Solid Worktop
- Ideal for meat and fish at the optimum storage temperature for each

ENERGY

HCR R2 V1

A<sup>+</sup>

239 kWh/annur

5 40°C-40%

\*

0°C

**86**L

\*\*\*

Adande Refrigeration

#### Storage Capacity

Gastronorm (GN) Pans 4 x 1/1 GN 100 mm Deep or equivalent (per Drawer)

Maximum Weight 40 kg of Food (per Drawer)

Volume 86 Litres (per Drawer)

#### **Climate Testing**

Tested to **Climate Class 4** (30°C & 55% relative humidity) for temperature and energy consumption and to **Climate Class 5** (40°C & 40% relative humidity) for temperature

#### Electrical

Mains Supply 230 Vac 50 Hz

Power Socket (included) Correct 2 or 3 Pin Plug fitted for each country

Mains Lead (included) 2 Metre Coiled Lead



### Options

CHEF BASE + HEAT SHIELD (HS)	High castor base (HC)		Standard castor base (C)		Small castor base (SC)		Rollers & feet base (R)		Small rollers & feet base (SR)		Fixed frame base (FF)	
Finished height	616 mm	HCR1/HCHS	545 mm	HCR1/CHS	524 mm	HCR1/SCHS	501 mm	HCR1/RHS	491 mm	HCR1/SRHS	590-900 mm	HCR1/FFHS
Load-bearing capacity	196 kg		273 kg		498 kg		299 kg		300 kg		185 kg	

For full options please see our Drawer Customising and Accessories pages

### Plan View

Chef base A+ fridge only (HCRI) With open drawer







