ADANDE.

Under counter

Standard drawers + cover top



Applications

- Bulk storage at the point of use
- · Ideal for meat, deli and larder prep
- Suitable for pastry and dessert prep
- Perfect storage for garnish and 'mise en place' generally
- Frozen storage next to deep fry station, with worktop mounted Fry Basket Rack as an optional extra


Hydrocarbon R600a Refrigerant

Standard drawer

'B' Energy Rating in Freezer Mode

'A' Energy Rating in Fridge Mode

(Consumption 307 kWh/annum)



Storage Capacity

Gastronorm (GN) Pans

4 x 1/1 GN 100 mm Deep or equivalent (per Drawer)

Maximum Weight

40 kg of Food (per Drawer)

Volume

86 Litres (per Drawer)

Climate Testing

Tested to Climate Class 4
(30°C & 55% relative humidity)
for temperature and energy
consumption and to Climate
Class 5 (40°C & 40% relative
humidity) for temperature

Flectrica

Mains Supply 230 Vac 50 Hz

Power Socket (included) Correct 2 or 3 Pin Plug fitted for each country

Mains Lead (included) 2 Metre Coiled Lead



Options

UNDER COUNTER + COVER TOP (T)	High castor base (HC)		Standard castor base (C)		Small castor base (SC)		Rollers & feet base (R)		Small rollers & feet base (SR)		Locking roller base (L)		Small locking roller base (SL)	
Finished height	962 mm	891 mm	VCD2/CT	870 mm	VCD2/CCT	846 mm	VODO/DT	836 mm	VODOLODI	846 mm	VODOLIT	836 mm	VODO/CLT	
Load-bearing capacity	0 kg	VCR2/HCT	0 kg	VCR2/CT	0 kg	VCR2/SCT	0 kg	VCR2/RT	0 kg	VCR2/SR1	0 kg	VCR2/LT	0 kg	VCR2/SLI

For full options please see our Drawer Customising and Accessories pages

Plan View

Under counter (VCR2)
With open drawer

Elevation

Under counter (VCR2) Standard castors (C) Cover top (T) VCR2/CT

878

